

PAPER • OPEN ACCESS

## Comprehensive review of geosynthetic clay liner and compacted clay liner

To cite this article: M Uma Shankar and M Muthukumar 2017 *IOP Conf. Ser.: Mater. Sci. Eng.* **263** 032026

View the [article online](#) for updates and enhancements.

### Related content

- [Recycling and reuse of chosen kinds of waste materials in a building industry](#)  
B Ferek, J Harasymiuk and J Tyburski
- [Reuse of dredged marine soils as landfill liner: Effect of pH on Escherichia coli growth](#)  
N M Anuar and C M Chan
- [Geosynthetics in geoenvironmental engineering](#)  
Werner W Müller and Fokke Saathoff

# Comprehensive review of geosynthetic clay liner and compacted clay liner

**Uma Shankar M, Muthukumar M**

School of Civil and Chemical Engineering, VIT University, Vellore, Tamil Nadu-632014, India

Email : mumashankar@vit.ac.in

**Abstract.** Human activity inevitably produces waste materials that must be managed. Some waste can be reused. However many wastes that cannot be used beneficially must be disposed of ensuring environmental safety. One of the common methods of disposal is landfilling. The most common problems of the landfill site are environmental degradation and groundwater contamination caused by leachate produced during the decomposition process of organic material and rainfall. Liner in a landfill is an important component which prevent leachate migration and prevent groundwater contamination. Earthen liners have been widely used to contain waste materials in landfill. Liners and covers for municipal and hazardous waste containment facilities are often constructed with the use of fine-grained, low plasticity soils. Because of low permeability geosynthetic clay liners and compacted clay liners are the main materials used in waste disposal landfills. This paper summaries the important geotechnical characteristics such as hydraulic conductivity, liquid limit and free swell index of geosynthetic clay liner and compacted clay liner based on research findings. This paper also compares geosynthetic clay liner and compacted clay liner based on certain criteria such as thickness, availability of materials, vulnerability to damage etc.

## 1. Introduction

Disposal of waste in an acceptable manner has been growing concerns to the public. One of the most significant concerns has been the possible contamination of groundwater from leachates generated by wastes. Landfilling is one waste management strategy adopted to dispose the waste in an effective and safe manner. Liner in an landfill plays an important role to prevent contaminant migration in to groundwater. Liner should have hydraulic conductivity less than  $10^{-7}$  cm/sec and its minimum thickness should be 600mm suggested by USEPA (United states of environmental protection agency). Some authors ([1] [2] [3]), suggest the other important functions of liners are to control pollutant migration for long term and should have low swelling shrinkage. These quality are satisfied by low permeably clayey soil at varying compaction. The most commonly used materials in sanitary landfill are compacted clay liner (CCL) and Geosynthetic clay liner (GCL). The main reason in using such materials is their low hydraulic conductivity which limits or eliminates the movement of not only the leachate from bottom of landfills but also the generated gases from the final cap of waste dumps.

Compacted clay liners are less expensive and it has good attenuation capacity. Hence it is used in most of the landfills. Though it has lot of desirable qualities for liners such low permeability and good attenuation capacity it has own demerits such as high swelling and shrinkage thus causing instability issue ([6][7]). On the other hand GCL has low hydraulic conductivity and can be easily installed. It



has good resistance against any environmental degradation (e.g free-thaw and wet-dry cycling) [8]. Geosynthetic clay liner (GCL) made up of thin layer of sodium bentonite or calcium bentonite sandwiched between two layers of geosynthetic materials.. Bentonite in GCL are made of granular or powder. GCL occupies minimum thickness of 5-10 mm. On the other hand CCL occupies 0.75-1m thick in the landfill.

GCL has numerous advantage compared to CCL in terms of low hydraulic conductivity. It need less skill labour for installation and less expensive. It also occupies less space compared to CCL. During freeze/thaw cycles GCL has good resistance hence it can be easily rectified. It also has good healing capacity when damaged during handling and installation. The small hole during installation are healed by bentonite in the GCL. It can be easily transported in the form rolls of 0.75 m in diameter and 4-6 m long. GCL proves to be less expensive compared to CCL where clay soil is far away from the landfill site. However CCL has large attenuation capacity compared to GCL because of its large thickness and it also inert to most of the permeant liquids that comes into contact. And also there is a possibility of geosynthetic component in GCL being degraded in the long term. According to Giroud (1996) some fungi and bacteria may catalyse the hydrolysis of polysters in GCL [11]. This paper summaries some important geotechnical properties such as hydraulic conductivity, Atterberg limits such as liquid and free swell index of GCL and CCL. It also presents the comparison of GCL and CCL.

## 2. Hydraulic conductivity of GCL and CCL

Hydraulic conductivity is an important component which controls leachate migration. In the case of GCL, the hydraulic performance mainly depends upon the hydraulic performance of bentonite. Bentonite occurs as a product of weathering, through chemical transformation from acid volcanic glass tufa (volcanic ashes), which has been deposited in sea water (Na-bentonite) or in fresh water (Ca-bentonite). High quality bentonite contains 65% to 95% montmorillonite mineral by weight [12]. Numerous research dealt with hydraulic performance of CCL and GCL when permeated with inorganic liquids ([13], [14], [15], [16], [17], [18],[19]) and also organic liquids ([20] [21] [22] [23]). Based on their experimental study it was found that permeability increased as concentration increased for clays with high plasticity. The hydraulic conductivity of clay when permeated with the high concentration liquid increases in significantly as that of when permeated with water ([24],[25] [26]). Most of the research either deals with bentonite or GCL. Jo et al. (2001) experimented the permeation of single species salt solutions such as LiCl, NaCl, KCl, CaCl<sub>2</sub> etc with GCL. The other study was the long term hydraulic performance of GCL with inorganic solutions such as calcium chloride, sodium chloride and potassium chloride [17]. GCL performance was investigated with permeation of non-standard liquids [26]. Bentonite hydraulic conductivity increases with increase in CaCl<sub>2</sub> solutions. Varying concentrations of CaCl<sub>2</sub> was permeated with GCL and was found that hydraulic conductivity of GCL increased as concentration of CaCl<sub>2</sub> increased[15].

Gleason et al. (1997) permeated different concentrations of CaCl<sub>2</sub>, NaCl and Methanol with different forms of Bentonite. One was Ca- Bentonite and another was Na- Bentonite. The result shows that Ca Benoitite has better resisting capacity as that of Na Bentonite. Higher concentration of calcium chloride results significant increase in hydraulic conductivity. Quality of clays an another important parameter studied by the researcher. Two bentonite one with higher quality and another with lower quality was permeated with water and CaCl<sub>2</sub> solutions. It was found that hydraulic performance of bentonite with higher quality was very much less than low quality bentonite when permeated with water but increases rapidly when permeated with CaCl<sub>2</sub> [16]. It was also found that high quality bentonite has higher resistance to chemicals compared to lower quality bentonite. Diffuse double increases with increase solute concentration. This results in flocculation of clays which leads to increase in hydraulic conductivity[28].

### 3. Liquid limit of GCL and CCL

Behaviour of clay was investigated by experimenting its consistency limits (Atterberg limits) [29]. Some researcher focussed on the Atterberg limits of clays of low plasticity (CL) and clay of high plasticity (CH). Plastic limit and liquid limit of CL increased with increase in solute concentration [30,31]. Plastic limit and liquid limit of low plastic soil increased on testing with NaOH. Increase in plastic limit and liquid limit could be attributed due to the formation of swelling compounds [32]. Increase in consistency limit of CL clay with increase solute concentration can be attributed with dispersion of clay particles. Increase in electrolyte concentration increases consistency limit of Marine clay. This may be due to dispersion of clay particles [33]. On the other hand clay with high plasticity its liquid limit decreases with increase in solute concentration [25, 28,34, 35,36]. Similar results were obtained with GCL. Its liquid limit decreased with increase in solute concentration. This is attributed due to flocculation and reduction in thickness of DDL on increase of electrolyte concentration. LL of GCL decreased from 530 to 96 when NaCl concentration increased. But its hydraulic conductivity increased from  $10^{-9}$  to  $10^{-6}$  cm when solute concentration increases [34].

### 4. Swell index of GCL and CCL

Many researcher focussed on correlation of hydraulic conductivity of bentonite with that swell potential [14,26,35,37,38,39]. Swell index of bentonite depends upon solute concentration and cation valency. The swell index of GCL decreased when concentration of electrolyte increased. On the other hand there is increase in hydraulic conductivity of GCL when concentration of permeant fluid increased. Hence strong correlation exist between hydraulic conductivity and Swell index. Increase in hydraulic conductivity is correlated with decrease swell index when permeated with higher solute concentration.

On the other hand few literatures are only available in case of swell index of CCL. Increase in solute concentration results decrease in thickness DDL and flocculation of clay particles which results decrease in swell index [14,16,40]. Volume changes of bentonite was studied on exposure of slat solution such as NaCl, CaCl<sub>2</sub>, KCl and re exposed to water [7]. Chemicals tends to decrease the thickness of DDL results in clay to flocculate [8].

### 5. Comparison of GCL and CCL

**Table 1** : Comparison of GCL and CCL

| Characteristic   | Geosynthetic clay liners  | Compacted clay liners  |
|--|---|--|
| Composition  | Bentonite, adhesives geotextiles and Geomembranes   | Native soils or blend of soil and bentonite  |
| Thickness  | Approximately 12 mm; consumes very little landfill volume   | Typically 300 to 600 mm; consumes more landfill volume   |
| Hydraulic conductivity   | Less than $10^{-8}$ cm/sec  | $\leq 1 \times 10^{-7}$ cm/s   |
| Speed and ease of construction   | Rapid and simple installation   | Slow and complicated construction  |
| Vulnerability to damage during construction from desiccation and freeze-thaw | GCLs are essentially dry; GCLs cannot desiccate during construction; not particularly vulnerable to damage from freeze-thaw | Compacted clay liners are nearly saturated; can desiccate during construction; vulnerable to damage freeze-thaw. |
| Vulnerability to damage from differential settlement                         | Can withstand much greater differential settlement than compacted clay liner  | Cannot withstand much differential settlement without cracking   |
| Materials  | Materials easily shipped to any site  | Suitable materials not available at all  |

|                     |  | sites  |
|---------------------|--|--|
| Cost                | Reasonably low, highly predicable cost that does not vary much from project to project | Highly variable—depends greatly on characteristics of locally soils                                |
| Ease of repair      | Ease of repair with patch place over problem area                                      | Very difficult to repair, must mobilize heavy earth-moving equipment if large area requires repair |
| Experience          | Limited to novelty   | Has been used for many years   |
| Regulatory approval | Equivalence in meeting performance objects   | Compacted clay liners are usually required by regulatory   |
| Fissures            | Cannot develop fissures if moisture available  | May develop fissures   |
| Weight              | Light weight   | Large weight   |

## 6. Conclusions

- Hydraulic conductivity of both GCL and CCL increases with increase in salt solution concentration for clay with high plasticity but hydraulic conductivity decrease for low plasticity clay soils when concentration of salt solution increased.
- As chemical concentration increased GCL liquid limit is decreased. However liquid limit of CCL made up of low plasticity clay increased with increase in chemical concentration and it decreased with increase in chemical concentration is due to dispersion and flocculation of clay particles.
- Swell index of GCL also decreased with increase in electrolyte concentration. However swell index of CCL was available only in few literature. Decrease in swell index with increase in solute concentration was due to flocculate formation of clay particles and decrease in DDL thickness.
- Finally GCL and CCL were compared based on criteria such as hydraulic conductivity, cost, vulnerability etc.

## References

- [1] Brandl, H. 1992. Mineral liners for hazardous waste containment. *Geotechnique* 42 57–65
- [2] Kayabaly, K., 1997. Engineering aspects of a novel landfill liner material: bentonite amended natural zeolite. *Engineering Geology* 46 105–114.
- [3] Cazaux, D., Didier, G., 2000. Field evaluation of hydraulic performances of geosynthetic clay liners by small and large-scale tests. *Geotextiles and Geomembranes* 18, 163–178.
- [4] Van Ree, C.C.D.F., Weststrate, F.A., Meskers, C.G., Bremmer, C.N., 1992. Design aspects and permeability testing of natural clay and sand-bentonite liners. *Geotechnique* 1 (42) 49–56.

- [5] Yahia, E.A.M., Amer, A.Al-R., Mohammed, Y.Al-A., Ahmed, Q., Abdul-Hamid, Al-R., 2005. Assessment of crushed shales for use as compacted landfill liners, *Engineering Geology* 80, 271–281.
- [6] Mitchell, J.K., 1993. *Fundamentals of Soil Behaviour*, second ed. John Wiley & Sons Inc..
- [7] Di Maio, C., Santoli, L., and Schiavone, P., 2004. Volume change behaviour of clays: the influence of mineral composition, pore fluid composition and stress state. *Mechanics of Materials* 36 (5–6), 435–451.
- [8] Bouazza, A. (2002). “Geosynthetic clay liners-A review”. *Geotextiles and Geomembranes* 20, 3–17.
- [9] Bouazza, A., (1997) Performance of geosynthetic clay liners, in *Proceedings of the First ANZ Conference on Environmental Geotechnics Melbourne, Australia*. p. 307-313.
- [10] Shan, H.-Y. and Chen, R H (2003) Effect of gravel subgrade on hydraulic performance of geosynthetic clay liner. *Geotextiles and Geomembranes*, 21(6): p. 339-354.
- [11] Giroud, J.P. (1996). “Granular Filters and Geotextile Filters”, *Proceedings of GeoFilters’96*,
- [12] Egloffstein, T. (1997) “Geosynthetic Clay Liners, Part Six: Ion Exchange,” *Geotechnical Fabrics Report, Industrial Fabrics Association International, Volume 15, No. 6*.
- [13] Jo, H.Y., Benson, C. H. and Edil, T. B. (2004). “Hydraulic conductivity and cation exchange in non-prehydrated and prehydrated bentonite permeated with weak inorganic salt solutions.” *Clays Clay Miner.*, 52(6), 661-679.
- [14] Kolstad, D., Benson, C.H., Edil, T.B. and Jo, H.Y. (2004a). “Hydraulic conductivity of a dense prehydrated GCL permeated with aggressive inorganic solutions”. *Geosynth. Int.*, 11(3), 233-241.
- [15] Lee, J.M., Shackelford, C.D., Benson, C.H., Jo, H.Y. and Edil, T.B. (2005). “Correlating index properties and hydraulic conductivity of geosynthetic clay liners.” *J.Geotech. Geoenviron. Eng.*, 131(11): 1319-1329.
- [16] Lee, J-M. and Shackelford, C.D. (2005). “Impact of bentonite quality on hydraulic conductivity of geosynthetic clay liners.” *J. Geotech Geoenviron. Eng.*, 131(1), 64–77.
- [17] Jo, H.Y., Benson, C. H., Shackelford, C. D., Lee, J-M. and Edil, T. B. (2005). “Long-term hydraulic conductivity of a geosynthetic clay liner (GCL) permeated with inorganic salt solutions.” *J. Geotech. Geoenviron. Eng.*, 131(4), 405–417.
- [18] Mishra, A.K., Ohtsubo, M., Li, L. and Higashi, T. (2005). “Effect of salt concentrations on the permeability and compressibility of soil-bentonite mixtures”. *J. Fac. Agr. Kyushu U.*, 50(2), 837-849.
- [19] Arasan, S.(2010) “ Effects of chemicals on geotechnical properties of clay liner” *Research journal of Applied Sciences, Engineering and Technology* 2(28) 765-775.
- [20] Anderson, D.C., Brown, K.W. and Thomas, J.C. (1985). “Conductivity of compacted clay soils to water and organic liquids.” *Waste Manage. Res.*, 3(1), 339-349.
- [21] Foreman, D.E. and Daniel, D.E. (1986). “Permeation of compacted clay with organic chemicals.” *J. Geotech. Eng.*, 112(7), 669-681.
- [22] Yong, R.N., E. Taheri, E. and Khodadadi, A.(2007). “Evaluation of remediation methods for soils contaminated with benzo [a] pyrene”. *Int. J. Environ. Res.*, 1(4), 341-346.
- [23] Park, J., Vipulanandan, C., Kim, J.W. and Oh, M.H. (2006). “Effects of surfactants and electrolyte solutions on the properties of soil.” *Environ. Geol.*, 49, 977-989.
- [24] Mitchell, J.K. and Madsen, F.T. (1987). “Chemical effects on clay hydraulic conductivity.” *Geotech. Practice Waste Disposal. ASCE*, 13, 87-116.
- [25] Shackelford, C. D. (1994). “Waste-soil interactions that alter hydraulic conductivity.” *Hydraulic conductivity and waste contaminant transport in soil, D. E. Daniel and S. J. Trautwein, eds., ASTM STP 1142, West Conshohocken, Pa., 111–168*
- [26] Shackelford, C.D., Benson, C.H., Katsumi, T., Edil, T.B. and Lin, L. (2000). “Evaluating the hydraulic conductivity of GCLs permeated with non-standard liquids”. *Geotext. Geomem.*, 18, 133-161.

- [27] Jo, H.Y., Katsumi, T., Benson, C. H. and Edil, T. B. (2001). “Hydraulic conductivity and swelling of nonprehydrated GCLs permeated with single-species salt solutions.” *J. Geotech. Geoenviron. Eng.*, 127(7), 557–567.
- [28] Gleason, M. H., Daniel, D. E. and Eykholt, G. R. (1997). “Calcium and sodium bentonite for hydraulic containment applications.” *J. Geotech. Geoenviron. Eng.*, 123(5), 438–445.
- [29] Jefferson, I. and C.D.F. Rogers, 1998. Liquid limit and the temperature sensitivity of clays. *Eng. Geol.*, 49:95-109
- [30] Arasan, S. and Yetimoglu, T. (2006). “Effect of leachate components on the consistency limits of clay liners.” National Soil Mechanics and Foundation Engineering Congress, Trabzon, Turkey, pp: 439-445.
- [31] Arasan, S. and Yetimoglu, T. (2008). “Effect of inorganic salt solutions on the consistency limits of two clays.” *Turk. J. Eng. Environ. Sci.*, 32, 107-115.
- [32] Sivapullaiah, P.V. and Manju, 2005. Kaolinite-alkali interaction and effects on basic properties. *Geotech. Geol. Eng.*, 23:601-214.
- [33] Rao, S.N. and P.K. Mathew, 1995. Effects of exchangeable cations on hydraulic conductivity of a marine clay. *Clays Clay Miner.*, 43(4): 433-437.
- [34] Petrov, R.J. and Rowe, R.K. (1997). “Geosynthetic Clay Liner (GCL)-chemical compatibility by hydraulic conductivity testing and factors impacting its performance.” *Can. Geotech. J.*, 34, 863-885
- [35] Lin, L.C. and Benson, C.H. (2000). “Effect of wet-dry cycling of swelling and hydraulic conductivity of GCLs.” *J. Geotech. Geoenviron. Eng.*, 126(1),40-49.
- [36] Sridharan, A. and Prakash, K. (2000). “Percussion and cone methods of determining the liquid limit of soils: Controlling mechanisms.” *Geotech. Test. J.*, 23 (2), 236–244.
- [37] Didier, G. and Comeaga, L. (1997). “Influence of initial hydration conditions on GCL leachate permeability”. Testing and acceptance criteria for geosynthetic clay liners, L. W. Well, ed., ASTM STP 1308, West Conshohocken, Pa., 181–195.